

How to put the seat cover on:

One of the most common problems I hear is how do I put the seat cover on. It is too tight. Do not despair- it will go on there. I have never met one I couldn't stretch over a seat frame. Once it is on it will stretch over the first few days.

Step 1: Open all straps and lay the seat cover straight.



Step 2: Put the seat plugs in the corners.



Step 3: Put the 2 top corners in. This will be tight and you will have to twist the seat cover around the top posts and just work a little bit at a time until fully inserted.



Step 4: Insert one of the lower corners.



Step 5: Turn the 4th corner **partially** inside out and flip it over the last corner. If this is really tight you can **CAREFULLY** use pliers for this step.



Step 6: Start attaching straps- it is best to start with the center one (the one that goes over the water bottle mounts). You should leave the straps fairly loose at this point. Attach all remaining straps.



Step 7: Start tightening straps- Get them as tight as you can because for the first week of riding or so they will stretch. After about a week or so they will need to be retightened. Once they are all tight remove the middle one and attach a water bottle cage (or two) if you like with small allen head screws and a nylon insert nut on the back. The strap goes over the cage, and will not interfere with taking the bottle in and out.



Seat Frame Adjustment

It is possible that your seat frame will need minor adjustment to make it fit perfectly in the frame. It is a simple very low tech procedure. There are two possible adjustments- first is to open up the slot a little. This is done with a small box wrench (10-12mm) Second adjustment is left and right. This can be done with an adjustable wrench. Patience will get you a perfect fit 😊

